



HHXX.EX15442 Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

[Page Bottom](#)

Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

[See General Information for Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze](#)

P T TRI SINAR PURNAMA

EX15442

DESA KEDUNG PANI
KELURAHAN WATES
KECAMATAN NGALIYAN
SEMARANG, 50188 INDONESIA

Malleable Iron Threaded Fittings (ANSI/ASME B16.3)

Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.3

Model.	Configuration	Size (in.)	Rated Pressure (psig)
BL	90° Elbows	1/8, 1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 6	300
BL45	45° Elbows	1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 6	300
BSL	90° Street Elbows	1/8, 1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
BSL45	45° Street Elbows	1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
RBL	90° Reducing Elbows	1/4 x 1/8, 3/8 x 1/4, 3/8 x 1/8, 1/2 x 3/8, 1/2 x 1/4, 3/4 x 1/2, 3/4 x 3/8, 3/4 x 1/4, 1 x 3/4, 1 x 1/2, 1 x 3/8, 1-1/4 x 1, 1-1/4 x 3/4, 1-1/4 x 1/2, 1-1/2 x 1-1/4, 1-1/2 x 1, 1-1/2 x 3/4, 2 x 1-1/2, 2 x 1-1/4, 2 x 1, 2 x 3/4, 2-1/2 x 1-1/2, 2-1/2 x 2, 3 x 2, 3 x 2-1/2, 4 x 3	300
BT	Tees	1/8, 1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 6	300
BTAS	Couplings	1/8, 1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
BRS	Couplings Reducing sizes	1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
BRCA	Caps	1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 3-1/2, 4, 6	300
BCR	Crosses	1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300
RBT	Reducing Tee	1/8 x 1/8 x 1/4; 1/4 x 1/4 x 1/8, 1/4 x 1/4 x 3/8; 3/8 x 1/4 x 1/4, 3/8 x 1/4 x 3/8, 3/8 x 3/8 x 1/4, 3/8 x 3/8 x 3/8, 3/8 x 3/8 x 1/2; 1/2 x 1/4 x 1/2, 1/2 x 1/2 x 1/4, 1/2 x 1/2 x 3/8, 1/2 x 3/8 x 3/8, 1/2 x 3/8 x 1/2; 1/2 x 1/4 x 1/2, 1/2 x 1/2 x 1/4, 1/2 x 1/2 x 3/8, 1/2 x 3/8 x 3/8, 1/2 x 3/8 x 1/2; 1/2 x 1/2 x 3/4, 1/2 x 1/2 x 1; 3/4 x 1/4 x 3/4, 3/4 x 3/8 x 3/8, 3/4 x 3/8 x 3/4, 3/4 x 1/2 x 3/8, 3/4 x 1/2 x 1/2, 3/4 x 1/2 x 3/4, 3/4 x 3/4 x 1/4, 3/4 x 3/4 x 3/8, 3/4 x 3/4 x 1/2, 3/4 x 3/4 x 1, 3/4 x 3/4 x 1-1/4; 1 x 1/2 x 1/2, 1 x 1/2 x 3/4, 1 x 1/2 x 1, 1 x 3/4 x 1/2, 1 x 3/4 x 3/4, 1 x 3/4 x 1, 1 x 1 x 1/4, 1 x 1 x 3/8, 1 x 1 x 1/2, 1 x 1 x 3/4, 1 x 1 x 1-1/4, 1 x 1 x 1-1/2, 1 x 1 x 2; 1-1/4 x 1/2 x 1, 1-1/4 x 1/2 x 1-1/4, 1-1/4 x 3/4 x 3/4, 1-1/4 x 3/4 x 1, 1-1/4 x 3/4 x 1-1/4, 1-1/4 x 1 x 1/2, 1-1/4 x 1 x 3/4, 1-1/4 x 1 x 1, 1-1/4 x 1 x 1-1/4, 1-1/4 x 1-1/4 x 3/8, 1-1/4 x 1-1/4 x 1/2, 1-1/4 x 1-1/4 x 3/4, 1-1/4 x 1-1/4 x 1, 1-1/4 x 1-1/4 x 1-1/2, 1-1/4 x 1-1/4 x 2; 1-1/2 x 1/2 x 1-1/2, 1-1/2 x 3/4 x 1/2, 1-1/2 x 3/4 x 1-1/2, 1-1/2 x 1 x 1, 1-1/2 x 1 x 1-1/4, 1-1/2 x 1 x 1-1/2, 1-1/2 x 1-1/4 x 1/2, 1-1/2 x 1-1/4 x 3/4, 1-1/2 x 1-1/4 x 1, 1-1/2 x 1-1/4 x 1-1/4, 1-1/2 x 1-1/4 x 1-1/2, 1-1/2 x 1-1/2 x 1/2, 1-1/2 x 1-1/2 x 3/4, 1-1/2 x 1-1/2 x 1, 1-1/2 x 1-1/2 x 1-1/4, 1-1/2 x 1-1/2 x 2; 2 x 3/4 x 2, 2 x 1 x 1-1/2, 2 x 1 x 2, 2 x 1-1/4 x 1-1/4, 2 x 1-1/4 x 1-1/2, 2 x 1-1/2 x 1, 2 x 1-1/2 x 1-1/4, 2 x 1-1/2 x 1-1/2, 2 x 1-1/2 x 2, 2 x 2 x 1/2, 2 x 2 x 3/4, 2 x 2 x 1, 2 x 2 x 1-1/4, 2 x 2 x 1-1/2, 2 x 2 x 2-1/2; 2-1/2 x 1-1/2 x 2, 2-1/2 x 1-1/2 x 2-1/2, 2-1/2 x 2 x 2, 2-1/2 x 2 x 2-1/2, 2-1/2 x 2-1/2 x 3/4, 2-1/2 x 2-1/2 x 1, 2-1/2 x 2-1/2 x 1-1/4, 2-1/2 x 2-1/2 x 1-1/2, 2-1/2 x 2-1/2 x 2; 3 x 2 x 2, 3 x 2 x 3, 3 x 3 x 3/4, 3 x 3 x 1, 3 x 3 x 1-1/4, 3 x 3 x 1-1/2, 3 x 3 x 2, 3 x 3 x 2-1/2; 4 x 4 x 1-1/2, 4 x 4 x 2, 4 x 4 x 2-1/2, 4 x 4 x 3; 6 x 6 x 2, 6 x 6 x 3, 6 x 6 x 4	300

Malleable Iron Threaded Fittings (ANSI/ASME B16.14)

Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.14

Model	Configuration	Size (in.)	Rated Pressure (psig)
PG	Square Head Plugs	1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	300
PG	Slotted Head Plug	4, 6	300
HBU	Outside & Inside Head Bushings	1/4 x 1/8, 3/8 x 1/4, 3/8 x 1/8, 1/2 x 3/8, 1/2 x 1/4, 1/2 x 1/8, 3/4 x 1/2, 3/4 x 3/8, 3/4 x 1/4, 3/4 x 1/8, 1 x 3/4, 1 x 1/2, 1 x 3/8, 1 x 1/4, 1 x 1/8, 1-1/4 x 1, 1-1/4 x 3/4, 1-1/4 x 1/2, 1-1/4 x 3/8, 1-1/4 x 1/4, 1-1/2 x 1-1/4, 1-1/2 x 1, 1-1/2 x 3/4, 1-1/2 x 1/2, 1-1/2 x 3/8, 1-1/2 x 1/4, 2 x 1-1/2, 2 x 1-1/4, 2 x 1, 2 x 3/4, 2 x 1/2, 2 x 3/8, 2 x 1/4, 2-1/2 x 2, 2-1/2 x 1-1/2, 2-1/2 x 1-1/4, 2-1/2 x 1, 1-1/2 x 3/4, 2-1/2 x 1/2, 3 x 1, 3 x 1-1/4, 3 x 1-1/2, 3 x 2, 3 x 2-1/2, 4 x 1, 4 x 1-1/4, 4 x 1-1/2, 4 x 2, 4 x 2-1/2, 4 x 3, 6 x 3, 6 x 4	300
LN	Locknuts	1/4, 3/8, 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2	300

Malleable Iron Fittings (BS143 & 1256)**Fittings fabricated with dimensional specifications in accordance with BS143 & 1256**

Model	Configuration	Size (in.)	Rated Pressure (psig)
A1	Reducing Elbows	1-1/4x1/2, 1-1/2x3/4, 2x1, 2x1-1/4	362 (25)
A1/45°	45° Elbows	2-1/2, 3, 4, 6	362 (25)
B1	Reducing Tees (Reducing on the Branch)	2-1/2x1/2, 2-1/2x3/4, 3x1/2, 3x3/4, 4x1, 4x1-1/4, 4x1-1/2, 4x2-1/2, 6x3, 6x4	362 (25)
B1	Reducing Tees (Increasing on the Branch)	2x2-1/2"	362 (25)
B1	Special Reducing Tees (Reducing on the Run & Branch)	2x1-1/2x1/2, 2-1/2x2x2	362 (25)
M2	Reducing Sockets	2-1/2x1-1/2, 2-1/2x1, 3x1, 6x3, 6x4	362 (25)
N4	Bushing	2-1/2x1/2, 2-1/2x3/4, 4x1, 4x1-1/4, 4x1-1/2, 6x2, 6x3, 6x4	362 (25)
N8	Hexagon Nipples	6	362 (25)
T1	Caps	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	362 (25)
T8	Plugs	6	362 (25)



Trademark and/or Tradename:

Last Updated on 2013-11-04[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2015 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2015 UL LLC".